
TECHNICAL DATA SHEET
PANDUIT PSL-BV BALL VALVE LOCKOUT

INTRODUCTION

This specification is intended to outline the physical and chemical properties of Panduit's PSL-BV ball valve lockout.

PRODUCTION SPECIFICATIONS

Description:	Molded Plastic Lockout available in two sizes for ball valves up to 3.0" [76 mm].
Standard Color:	Red
<i>REV</i>	
Service Temperature Range:	-40 F to 212 F (-40C to 100C). Do not impact at -40deg.
Shelf Life:	Indefinite when stored at 70° F (21° C) and 40% to 50% R.H.
Substrate Type:	Polypropylene
Chemical Resistance:	

Reagent	Resistance
Sulfuric Acid	Excellent
Hydrochloric Acid	Excellent
Sodium Hydroxide	Excellent
Methyl Ethyl Ketone	Excellent
Acetone	Excellent
1,1,1 Trichloroethane	Moderate damage
Methanol	Excellent
IPA (Isopropanol)	Excellent
Toluene	Little Damage
Glacial Acetic Acid	Excellent
Diesel Fuel	Excellent
Heptane	Failed
Cellosolve Acetate	Excellent
Ammonia	Excellent
Turpentine	Little damage
Kerosene	Little damage
Water	Excellent
Gasoline	Little damage

