
TECHNICAL DATA SHEET
PANDUIT PSL-CB AND PSL-CBIL CIRCUIT BREAKER LOCKOUTS

INTRODUCTION

This specification is intended to outline the physical and chemical properties of Panduit's PSL-CB and PSL-CBIL circuit breaker lockouts.

PRODUCTION SPECIFICATIONS

Description:	Molded Plastic circuit breaker lockout with stainless steel set screw.
Standard Color:	Red for lockout body.
Service Temperature Range:	-40 to 250 F
Shelf Life:	Indefinite when stored at 70° F (21° C) and 40% to 50% R.H.
Substrate Type:	Glass Filled Nylon for lockout body. 18-8 stainless steel set screw.

Chemical Resistance:

Reagent	Resistance
Sulfuric Acid	Excellent
Hydrochloric Acid	Excellent
Sodium Hydroxide	Excellent
Methyl Ethyl Ketone	Excellent
Acetone	Excellent
1,1,1-Trichloroethane	Excellent
Methanol	Excellent
IPA (Isopropanol)	Excellent
ASTM #3 Oil	Excellent
SAE 20 Oil	Excellent
Alconox	Excellent
Toluene	Excellent
Mineral Spirits	Excellent
Glacial Acetic Acid	Excellent
Diesel Fuel	Excellent
Heptane	Excellent
Cellosolve Acetate	Excellent
Ammonia	Excellent
Turpentine	Excellent
Kerosene	Excellent
Water	Excellent
Gasoline	Excellent