
**TECHNICAL DATA SHEET
PANDUIT PSL-MLDC LOCKOUT CABLE**

INTRODUCTION

This specification is intended to outline the physical and chemical properties of Panduit's PSL-MLDC lockout cable.

PRODUCTION SPECIFICATIONS

- Description:** Vinyl coated galvanized steel cable with loophole to be used with PSL-MLD lockout device.
- Standard Color:** Red
- Service Temperature Range:** -9° F to 176° F (-23° C to 80° C)
- Shelf Life:** Indefinite when stored at 70° F (21° C) and 40% to 50% R.H.
- Substrate Type:** Vinyl coated galvanized steel cable
- Chemical Resistance:**

Reagent	Resistance
Sulfuric Acid 20%	Good-Excellent
Hydrochloric Acid 20%	Good-Excellent
Sodium Hydroxide 50%	Failed
Methyl Ethyl Ketone	Failed
Acetone	Failed
1,1,1 Trichloroethane	Failed
Methanol	Good-Excellent
Toluene	Failed
Mineral Spirits	Little Damage
Glacial Acetic Acid	Good-Excellent
Diesel Fuel	Failed
Cellosolve Acetate	Failed
Ammonia	Good-Excellent
Turpentine	Good-Excellent
Kerosene	Excellent
Water	Excellent
Gasoline	Good

**TECHNICAL DATA SHEET
PANDUIT PSL-MLDC LOCKOUT CABLE**

REVISION HISTORY

Rev. Number	Rev. Date	ECN Number	Description
1	10/9/2009	5876	Service Temperature Range: -9°F (-23°C) was -22°F (-22°C) ---- Error Correction