

---

**TECHNICAL DATA SHEET  
PANDUIT PSL-V GATE VALVE LOCKOUT**

---

**INTRODUCTION**

This specification is intended to outline the physical and chemical properties of Panduit's PSL-V gate valve lockouts.

**PRODUCTION SPECIFICATIONS**

- Description:** Gate Valve Lockout in four colors and five sizes to fit valve handles up to 13.0" [330mm].
- Standard Color:** Red for Lockout Body.
- Service Temperature Range:** -40 F to 212 F (-40C to 100C) Do not impact at -40 deg.
- Shelf Life:** Indefinite when stored at 70° F (21° C) and 40% to 50% R.H.
- Substrate Type:** Polypropylene
- Chemical Resistance:**

<b>Reagent</b>	<b>Resistance</b>
Sulfuric Acid	Excellent
Hydrochloric Acid	Excellent
Sodium Hydroxide	Excellent
Methyl Ethyl Ketone	Excellent
Acetone	Excellent
1,1,1-Trichloroethane	Moderate damage
Methanol	Excellent
IPA (Isopropanol)	Excellent
Toluene	Little damage
Glacial Acetic Acid	Excellent
Diesel Fuel	Excellent
Heptane	Failed
Cellosolve Acetate	Excellent
Ammonia	Excellent
Turpentine	Little damage
Kerosene	Little damage
Water	Excellent
Gasoline	Little damage